




# RADDITAL

[www.raddital.com](http://www.raddital.com)

## DBM100-TH

### POWER RECTIFIER BRIDGE

Output Current      100 A



$V_{RRM}$	$V_{RSM}$	P/N
1600	1700	DBM100.16-TH

#### Features







Low forward voltage diodes for high surge capability  
Low thermal impedance packaging  
Electrically insulated case

#### Applications

Input rectifier for variable frequency drives  
Battery charger rectifiers  
Three phase rectifier for power supplies  
Rectifiers for DC motor fields supplies

Diodes characteristics		Conditions	$T_j [^{\circ}\text{C}]$	Value
$I_{RRM}$	Max repetitive peak reverse current	$V = V_{RRM}$	150	4 mA
$V_F(TO)$	Threshold voltage		150	0,9 V
$r_F$	Forward slope resistance		150	3,5 m $\Omega$
$V_{FM}$	Peak forward voltage, max	$I_F = 100\text{A}$	25	1,7 V
$I_{FSM}$	Surge forward current	Half sine wave, 10 ms	150	1200 A
$I^2t$	Max $I^2t$ for fusing		150	7200 A <sup>2</sup> s
$T_{jmax}$	Operating junction temperature			-40 / 150 °C
$R_{th(j-c)}$	Thermal resistance (junction to case)	DC operation		0,52 °C/W
$R_{th(j-c)}$	Thermal resistance (junction to case)	Rectangular wave 120° conduction		0,58 °C/W

Module characteristics		Conditions	Value
$I_D$	DC output current	$T_c = 125\text{ }^{\circ}\text{C}$	100 A
$I_D$	DC output current	$T_a = 40\text{ }^{\circ}\text{C} ; \text{freely suspended}$	8 A
$V_{INS}$	RMS Insulating voltage	$50 / 60\text{ Hz } t = 1\text{ s } (i < 1\text{ mA})$	3600 V
$V_{INS}$	RMS Insulating voltage	$50 / 60\text{ Hz } t = 60\text{ s } (i < 1\text{ mA})$	3000 V
$R_{th(j-c)}$	Thermal resistance (junction to case)	DC operation	0,087 °C/W
$R_{th(j-c)}$	Thermal resistance (junction to case)	Rect. wave 120° conduction	0,097 °C/W
$R_{th(c-h)}$	Thermal resistance (case to heatsink)	Mounting surface flat, smooth and greased	0,085 °C/W
$R_{th(j-a)}$	Thermal resistance (junction to ambient)	Freely suspended or mounted on an insulator	8,5 °C/W
$R_{th(j-a)}$	Thermal resistance (junction to ambient)	Mounted on a painted metal sheet 250x250x1 mm	3,0 °C/W
$T_{stg}$	Max storage temperature		150 °C
$W$	Weight		120 g
$M_1$	Mounting torque, ± 15 %		4,5 N·m
			40 lb·inch



### Notes :

To reduce the thermal resistance we recommend to apply a layer of 100..200 $\mu$ m of thermal compound to the heat sink or to the module base.

The flatness tolerance of IMS is 80 $\mu$ m.

**DBM100.16-LL-FIX5-LP-P49,35-TH**  
**Code:DBM70000100040**

RADDITAL srl reserves the right to change any specification without notice

**RADDITAL srl Via Magellano,4 26861 Fombio(LO)-IT**

Phone:+39 0377 379298 Fax:+39 0377 33590

issue:mar-2017